

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claim 1 (Previously Presented): A method comprising:

receiving at a mobile terminal a first digital video broadcasting signal broadcast by a first wireless transmitter at a first frequency;

when said first digital video broadcasting signal meets a first predefined criterion, the mobile terminal deriving digital video broadcasting signal data from a second digital video broadcasting signal broadcast by a second wireless transmitter; and

determining at the mobile terminal that said digital video broadcasting signal data from said second wireless transmitter meets a second predefined criterion, the mobile terminal switching reception from said first wireless transmitter to said second wireless transmitter after a first digital video broadcasting signal transmission burst has been received and before a second digital video broadcasting signal transmission burst has been received.

Claim 2 (Canceled).

Claim 3 (Currently Amended): A method as in claim 1 further comprising ~~the step of~~ stripping encapsulation from said first digital video broadcasting signal after receipt by the mobile terminal.

Claim 4 (Original): A method as in claim 3 wherein said encapsulation conforms to standard EN 301192.

Claim 5 (Currently Amended): A method as in claim 3 further comprising ~~the step of~~ sending said first digital video broadcasting signal to an application processor for conversion to a data packet.

Claim 6 (Previously Presented): A method as in claim 1 wherein said first criterion is met if a receiver signal strength value for said first digital video broadcasting signal measured by the mobile terminal is less than a predetermined value.

Claim 7 (Previously Presented): A method as in claim 1 wherein said first criterion is met if a bit error rate for said first digital video broadcasting signal measured by the mobile terminal is greater than a predetermined value.

Claim 8 (Previously Presented): A method as in claim 1 wherein said second criterion is met if a bit error rate for said second digital video broadcasting signal measured by the mobile terminal is smaller than a predetermined value.

Claim 9 (Currently Amended): An mobile terminal apparatus comprising:  
a digital broadcast receiver ~~suitable for receiving~~ configured to receive digital video broadcasting information from a plurality of wireless transmitters, wherein said digital broadcast receiver is configured to receive from a first transmitter at least a first portion of the digital video broadcasting information as a first transmission burst, said first transmission burst broadcast by the first wireless transmitter and a second wireless transmitter;  
a receiver elastic buffer ~~for storing~~ configured to store said first transmission burst; and  
~~means an election module configured to switch for switching~~ reception of the mobile terminal from the first wireless transmitter to the second wireless transmitter after reception of said first transmission burst has been completed.

Claim 10 (Currently Amended): The mobile terminal apparatus as in claim 9 further comprising ~~means a module configured to derive~~ for deriving a bit error rate for said first transmission burst.

Claim 11 (Currently Amended): The ~~mobile-terminal~~apparatus as in claim 9 further comprising ~~means-a module configured to derive~~for deriving a received signal strength indicator value for said first transmission burst.

Claim 12 (Currently Amended): The ~~mobile-terminal~~apparatus as in claim 9 wherein said ~~means-election module configured to switch~~for switching is operative in response to said second wireless transmitter providing to said mobile terminal a signal meeting a predefined criterion.

Claim 13 (Currently Amended): The ~~mobile-terminal~~apparatus as in claim 9 further comprising an application processor ~~for converting~~configured to convert said first transmission burst into an information data stream.

Claim 14 (Currently Amended): The ~~mobile-terminal~~apparatus as in claim 9 further comprising a stream filter ~~for stripping~~configured to strip transmission encapsulation from said first transmission burst stored in said receiver elastic buffer.

Claim 15 (Currently Amended): The ~~mobile-terminal~~apparatus as in claim 14 wherein said stream filter comprises an Internet protocol (IP) filter.

Claim 16 (Currently Amended): A ~~digital-broadcasting~~ system comprising:  
a first transmitter ~~for broadcasting~~configured to broadcast at least an interval of digital video broadcasting information as a transmission burst; and  
a receiver system ~~for receiving~~configured to receive said transmission burst, said receiver including a receiver elastic buffer for buffering said transmission burst, said receiver further including ~~means-a module configured to execute~~for executing a hand-over from said first transmitter to at least one other transmitter upon receipt of said transmission burst if at least one predefined criterion has been met.

Claim 17 (Currently Amended): The ~~digital broadcasting~~ system as in claim 16 wherein said first transmitter comprises a multi-protocol encapsulator for encapsulating said transmission burst.

Claim 18 (Currently Amended): The ~~digital broadcasting~~ system as in claim 16 wherein said at least one predefined criterion is met if a receiver signal strength value for said transmission burst as measured by said receiver system is less than a predetermined value.

Claim 19 (Currently Amended): The ~~digital broadcasting~~ system as in claim 16 wherein said at least one predefined criterion is met if a bit error rate for said transmission burst as measured by the receiver system is greater than a predetermined value.

Claim 20 (Currently Amended): The ~~digital broadcasting~~ system as in claim 16 wherein said at least one predefined criterion is met if a bit error rate for a signal received from said at least one other transmitter as measured by the receiver system is smaller than a predetermined value.

Claim 21 (Currently Amended): A method comprising:  
a mobile terminal configured to receive a series of signals provided by each of a plurality of wireless transmitters, said mobile terminal selecting a first wireless transmitter from the plurality of wireless transmitters for providing digital video broadcasting information, each of said wireless transmitters broadcasting on a different frequency;  
receiving by the mobile terminal, signals broadcast by the first wireless transmitter;  
the mobile terminal ~~deriving~~configured to derive a first bit error rate for digital video broadcasting information received ~~from~~from said first wireless transmitter;  
when said first bit error rate for said first wireless transmitter is greater than a predefined quasi-error-free value, the mobile terminal deriving a second bit error rate for a second wireless transmitter; and

when said second bit-error rate is less than said quasi-error-free value, the mobile terminal selecting said second wireless transmitter for providing the digital video broadcasting information, and switching reception to said second wireless transmitter.

Claim 22 (Previously Presented): The method of claim 21 wherein said step of selecting said second synchronized wireless transmitter for providing information is performed after completing receipt of a signal transmission burst from said first synchronized wireless transmitter and prior to a consecutive signal transmission burst from said second synchronized wireless transmitter.

Claim 23 (Previously Presented): The method as in claim 21 wherein said second synchronized wireless transmitter is selected from the plurality of synchronized wireless transmitters as a function of received signal strength indicator value.

Claim 24 (Currently Amended): An mobile-terminal apparatus comprising:

a digital broadcast receiver ~~that receives~~configured to receive digital video broadcasting information from a plurality of synchronized digital video broadcasting wireless transmitters, wherein each synchronized transmitter synchronously transmits information or data produced by a common service provider ~~a common content signal~~, said digital broadcast receiver further configured to receive at least a first portion of the digital video broadcasting information as a first transmission burst, said first transmission burst broadcast by a first digital video broadcasting wireless transmitter of the plurality of wireless transmitters;

a buffer configured to store said first transmission burst;

a processor coupled to the digital broadcast receiver; and

memory storing executable instructions that, when executed by the processor, causes the ~~mobile-terminal apparatus~~ to switch reception by the digital broadcast receiver from the first digital video broadcasting wireless transmitter to a second digital video broadcasting wireless transmitter of the plurality of wireless transmitters after reception of said first transmission burst

has been completed and before a consecutive transmission burst is sent by the plurality of synchronized ~~first and second~~ digital video broadcasting wireless transmitters.

Claim 25 (Currently Amended): The ~~mobile-terminal~~apparatus of claim 24, wherein the executable instructions are further for deriving a bit error rate for said first transmission burst.

Claim 26 (Currently Amended): The ~~mobile-terminal~~apparatus of claim 24, wherein the executable instructions are further for deriving a received signal strength indicator value for said first transmission burst.

Claim 27 (Currently Amended): The ~~apparatus~~mobile-terminal of claim 24, wherein said switching is operative in response to said second digital video broadcasting wireless transmitter providing to said ~~mobile-terminal~~apparatus a signal meeting a predefined criterion.

Claim 28 (Currently Amended): The ~~apparatus~~mobile-terminal of claim 24, wherein the executable instructions are further for converting said first transmission burst into an information data stream.

Claim 29 (Currently Amended): The ~~apparatus~~mobile-terminal of claim 24, further comprising a stream filter configured to strip transmission encapsulation from said first transmission burst stored in said buffer.

Claim 30 (Currently Amended): The ~~apparatus~~mobile-terminal of claim 29, wherein said stream filter comprises an Internet Protocol (IP) filter.

Claim 31 (Currently Amended): A ~~digital broadcasting system~~ comprising:  
a first digital video broadcasting transmitter configured to broadcast digital video broadcasting information as a first plurality of consecutive transmission bursts;

a second digital video broadcasting transmitter configured to broadcast the digital video broadcasting information as a second plurality of consecutive transmission bursts in synchronization with the first plurality of consecutive transmission bursts; and

a receiver system configured to receive said digital video broadcasting information, said receiver system including a buffer configured to buffer said transmission bursts, said receiver further including a processor, and a memory storing executable instructions that, when executed by the processor, cause the processor to perform a hand-over from said first digital video broadcasting transmitter to said second digital video broadcasting transmitter upon receipt of a first transmission burst, prior to a consecutive transmission burst, if at least one predefined criterion has been met.

Claim 32 (Currently Amended): The ~~digital broadcasting~~ system of claim 31, wherein said first digital video broadcasting transmitter comprises a multi-protocol encapsulator configured to encapsulate each transmission burst.

Claim 33 (Currently Amended): The ~~digital broadcasting~~ system of claim 31, wherein said at least one predefined criterion is met if a receiver signal strength value for said first transmission burst as measured by said receiver system is less than a predetermined value.

Claim 34 (Currently Amended): The ~~digital broadcasting~~ system of claim 31, wherein said at least one predefined criterion is met if a bit error rate for said first transmission burst as measured by the receiver system is greater than a predetermined value.

Claim 35 (Currently Amended): The ~~digital broadcasting~~ system of claim 31, wherein said at least one predefined criterion is met if a bit error rate for a signal received from said second digital video broadcasting transmitter as measured by the receiver system is smaller than a predetermined value.

Claim 36 (Currently Amended): ~~A method for receiving a series of digital video broadcasting signals provided by each of first and second wireless transmitters, said method comprising:~~

a mobile terminal receiving digital video broadcasting signals broadcast by ~~the~~ a first wireless transmitter and a second wireless transmitters, each of said first and second wireless transmitters broadcasting on a different frequency;

the mobile terminal selecting the first wireless transmitter for receiving digital video broadcasting information broadcast in consecutive transmission bursts;

deriving by the mobile terminal a first bit error rate for digital video broadcasting information received from said first wireless transmitter;

if said first bit error rate for said first wireless transmitter is greater than a predefined quasi-error-free value, the mobile terminal deriving a second bit-error-rate for the second wireless transmitter; and

if said second bit error rate is less than said quasi-error-free value, the mobile terminal selecting said second wireless transmitter for receiving the digital video broadcasting information, and switching reception to said second wireless transmitter.

Claim 37 (Previously Presented): The method of claim 36, wherein said step of selecting said second wireless transmitter for receiving the information is performed after receipt of a signal transmission burst from said first wireless transmitter, and prior to receipt of a consecutive signal transmission burst from said second wireless transmitter.

Claim 38 (Previously Presented): The method as in claim 36, wherein said second wireless transmitter is selected from a plurality of available transmitters as a function of a received signal strength indicator value.

Claim 39 (Currently Amended): ~~The digital broadcasting system of claim 16, wherein the receiver system comprises a mobile terminal.~~



Claim 40 (Currently Amended): The ~~digital-broadcasting-system~~ of claim 16, wherein executing a hand-over from said first transmitter to said at least one other transmitter upon receipt of said transmission burst comprises completing the hand-over prior to a consecutive transmission burst transmitted by the synchronized first and other transmitters.

Claim 41 (Previously Presented): The method of claim 1, wherein each of the plurality of wireless transmitters broadcast in synchronization.

Claim 42 (Previously Presented): The method of claim 41, wherein switching reception from said first wireless transmitter to said second wireless transmitter after the first digital video broadcasting service signal transmission burst has been received occurs prior to receipt of a consecutive digital video broadcasting service signal transmission burst transmitted by the second wireless transmitter.

Claim 43 (Canceled).

Claim 44 (Currently Amended): The ~~mobile-terminal~~apparatus of claim 9, wherein means the election module for switching reception from the first wireless transmitter to the second wireless transmitter synchronized with the first wireless transmitter switches reception after reception of said first transmission burst has been completed and prior to a consecutive transmission burst transmitted by the second wireless transmitter.

Claim 45 (Canceled).